


# CMS-2200

## Cinema Media Server with Solid State Storage



(Android based Screen Management System)



The high frame rate Cinema Media Server for the digital cinema industry supports JPEG-2000 decoding of 4K and high frame rate 2K images with state-of-the-art solid state storage



Monarch butterflies are found throughout coastal San Luis Obispo County with Pismo State Beach being one of the largest monarch groves in the United States.

181 Bonetti Drive  
San Luis Obispo, CA 93401-7397 USA  
(Ph) +1 805.549.0161 (Fax) +1 805.549.0163  
uslinc@uslinc.com www.uslinc.com



# Cinema Media Server

## ○ ○ ○ ○ ● SPECIFICATIONS

- Combined IMB with solid state storage
- 1.536 TB, 2TB, or 3TB solid state storage available ingest with two USB 3.0 or eSATA
- JPEG-2000 decoding up to 500 Mb/s
  - 2K 2D 24fps to 60fps
  - 2K 3D 24fps to 60fps
  - 4K 2D 24fps to 30fps
- AES-128 decryption/HMAC-SHA1
- MPEG-2 decoding up to 120 Mb/s
- Two HD-SDI inputs and two HDMI inputs
- Dual 1 Gb copper and fiber data ports for live content streaming
- Auxiliary control port (RJ45)
- Built in automation with optional expansion module
- Sixteen channel digital audio
- Sync input and output for large screen presentations
- Civolution image and audio forensic marking
- FIPS, DCI, and CE & FCC compliant

## SMS Screen Management System



- Includes SMS cross platform for Android, iOS and Windows.
- Intuitive touch screen interface, ideal for portable devices.
- Can be installed on desktop or laptop computers.
- Simple integrated automation interface with predefined and user defined actions.
- User access control with administrative supervision settings.
- Supports multiple auditoriums, may be used as a management workstation.

## CMSA Automation



- CMSA automation with 10 Isolated solid state relays momentary outputs (160mA@48V, AC/DC).
- CMSA automation with 2 Relay outputs (10A, 230 VAC). Momentary or latching.
- 2 Inputs - start/stop, fire alarm, etc.
- LED verification of all actions.
- Local pushbutton control/override.
- RJ-45 interface to CMS-2200.
- Rack or Wall mount - with optional remote panel.