





SR-800

Cinema Surround Loudspeaker



The SR-800 Cinema Surround Loudspeaker is a two-way design that features an 8" (203mm) low-frequency transducer with a 1" dome tweeter. The 125 watt continuous power rating and sophisticated crossover circuitry provides absolute reliability.

The SR-800 is designed for safe and secure mounting. The cabinet is constructed of 12mm MDF with internal bracing for superior structural integrity. The rear panel of the cabinet is fitted with four threaded insert mounting points that accommodate the standard bolt pattern for most third- party bracket manufacturers. Included pre- installed speaker side hardware allows fast single-installer wall mounting, and brackets support down-angles of either 15° (QM-SW, ordered separately) or 23° (QM-BW, ordered separately). A traditional U-bracket "yoke" style bracket (YM-300) is also available.

The compact black enclosure with black grille blends into any theatre decor.

Resources

Documents

Drawings

Image Gallery

Features

- High Performance for all Cinema applications
- 8" (203 mm) woofer
- 1" (25 mm) dome tweeter
- Pre-installed speaker-side OM mounting hardware
 19

Shares

SPECIFICATIONS	SR-800		
Frequency Range ¹ (-10dB, Half space)	60 Hz to 20 kHz		
Rated Coverage Angle (-6 dB)	135° conical		
Maximum Rated SPL ⁴ Calculated Peak at rated power Calculated Continuous	117 dB 111 dB		
Rated Impedance	8 ohms		
Rated Noise Power ² Recommended Amplifier Power	125 watts 400 watts		
Sensitivity ³	90 dB		
Input Connector	Two 5-way binding posts, accepts up to #10 AWG stranded wire		
Transducers	8" (203 mm) LF driver		
	1" (25 mm) dome tweeter		
Enclosure Material	12mm MDF with black vinyl wrap, matte finish		
Dimensions (HWD) inches	14.4 × 11.7 × 9 inches		

SPECIFICATIONS	SR-800
Dimensions (HWD) mm	365 × 298 × 228.5 mm
Net Weight	14.3 lb (6.5 kg)
Brackets	QM-SW, QM-BW, YM-300

¹ Free-field, -10 dB from on-axis sensitivity

Specifications are subject to change without notice.

Join the Community	About	Help
Q-SYS	Our Story	Support Q-SYS QSC Audio
	Our Vision	Training Q-SYS QSC Audio
	Our Values	Product Registration
	Our Leadership	Warranty Statement
QSC Audio	Careers	Acuity Security Vulnerability Policy
	News Q-SYS QSC Audio	
	Our Impact / ESG	
	Acuity	

Contact Us

Contact QSC Corporate

Contact Q-SYS

Contact QSC Audio

©2025 QSC, LLC all rights reserved

Trademark Usage | Privacy Notice | Cookie Policy | Cookie Preferences | California Transparency in Supply Chains Act

² AES2-1984 noise signal for 2 Hrs

³ On-axis, free-field sensitivity, 1W, 1 m

⁴ Calculated from rated noise voltage and sensitivity